# DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid

Version 4.1

Revision Date 02/06/2014

Ref. 13000000559

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Tradename/Synonym	:	DuPont <sup>™</sup> VERTREL <sup>®</sup> XF specialty fluid Vertrel <sup>®</sup> 4310 HFC-43-10mee HFC-4310	
MSDS Number	:	13000000559	
Product Use	:	Cleaning agent	
Manufacturer	:	DuPont 1007 Market Street Wilmington, DE 19898	
Product Information Medical Emergency Transport Emergency	:	1-302-774-1000 1-800-441-3637 (outside the U.S. 1-302-774-1139) CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)	

#### **SECTION 2. HAZARDS IDENTIFICATION**

**Emergency Overview** 

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Prolonged skin contact may defat the skin and produce dermatitis. Effects of breathing high concentrations of vapour may include: May cause cardiac arrhythmia.

Misuse or intentional inhalation abuse may lead to death without warning.

Potential Health Effects Inhalation

1,1,1,2,2,3,4,5,5,5Decafluoropentane

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects. Other symptoms potentially related to misuse or inhalation abuse are: Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness, Convulsions. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

# DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid

#### Version 4.1

Revision Date 02/06/2014

Ref. 13000000559

Repeated exposure 1,1,1,2,2,3,4,5,5,5-Decafluoropentane

: Adverse effects from repeated inhalation may include: Central nervous system effects

## Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	138495-42-8	100 %

ECTION 4. FIRST AID ME	ASURES
Skin contact	: Take off all contaminated clothing immediately. Wash off with warm water.
Eye contact	<ul> <li>In case of eye contact Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary. Consult a physician.
Ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. If vomiting occurs, have victim lean forward to reduce the risk of aspiration. Consult a physician.
General advice	: Never give anything by mouth to an unconscious person. Victim to lie down in the recovery position, cover and keep him warm. Give oxygen or artificial respiration if needed. When symptoms persist or in all cases of doubt seek medical advice.
	2/8

Material Safety Data Shee	t	QU PONT.
<b>DuPont<sup>™</sup> VERTREL<sup>®</sup> XF</b> Version 4.1	- S	pecialty fluid
Revision Date 02/06/2014		Ref. 13000000559
Notes to physician	:	Do not give adrenaline or similar drugs.
SECTION 5. FIREFIGHTING MEA	SU	RES
Flammable Properties Flash point	:	Tag closed cup Method : ASTM D 56 does not flash
Lower explosion limit/ lower flammability limit	:	Method : None per ASTM E681
Upper explosion limit/ upper flammability limit	:	Method : None per ASTM E681
Fire and Explosion Hazard	:	Pressure build-up. Fire or intense heat may cause violent rupture of packages.
		Hazardous combustion products: Hydrogen fluoride Fluorinated hydrocarbons Carbonyl fluoride Carbon oxides
		The product is not flammable.
Suitable extinguishing media	:	Water spray, Water mist, Dry chemical, Carbon dioxide (CO2)
Firefighting Instructions	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire. Exposure to decomposition products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
SECTION 6. ACCIDENTAL RELEA	AS	E MEASURES
		IEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. DTECTIVE EQUIPMENT during clean-up.
Safeguards (Personnel)	:	Evacuate personnel to safe areas. Ventilate area, especially low or enclosed 3 / 8
		3/0



# DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid

Version 4.1

Revision Date 02/06/2014 Ref. 13000000559	
places where heavy vapours might collect. In case of insufficient ventilation, wear suitable respiratory equipment. Refer to protective measures listed in sections 7 and 8.	
Spill Cleanup : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).	
Accidental Release Measures : Prevent further leakage or spillage. Prevent spreading over a wide area (e.g. by containment or oil barriers). Should not be released into the environment.	
SECTION 7. HANDLING AND STORAGE	
<ul> <li>Handling (Personnel)</li> <li>Avoid contact with skin, eyes and clothing. Avoid breathing vapours or mist. Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday.</li> </ul>	
<ul> <li>Handling (Physical Aspects)</li> <li>Material should not be dispensed from its container by pouring, except for small sample containers where fume hoods or where other ventilation is used to manage the exposure limits. The use of a drum pump is recommended for dispensing from shipping containers.</li> </ul>	
Storage : Protect from contamination. Keep container tightly closed in a dry and well- ventilated place. Store in original container. Avoid freezing temperatures. If stored below -10 ℃ (14 °F), mix prior to use.	
Storage temperature : < 52 °C (< 126 °F)	
SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION	
Engineering controls : Use sufficient ventilation to keep employee exposure below recommended limits.	
Personal protective equipment Respiratory protection : For rescue and maintenance work in storage tanks use self-contained breathing apparatus. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.	
4 / 8	

Material Safety Data Sheet



# DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid

Version 4.1

Revision Date 02/06/2014		Ref. 13000	0000559
Hand protection	: Material:	Solvent-resista	ant gloves
Eye protection	possibilit		e-shields Additionally wear a face shield where the e contact due to splashing, spraying or airborne al.
Skin and body protection	: Protectiv	e suit	
Exposure Guidelines Exposure Limit Values			
1,1,1,2,2,3,4,5,5,5-Deca AEL *	fluoropentane (DUPONT)	200 ppm	8 & 12 hr. TWA
AEL *	(DUPONT)	400 ppm	Ceiling Limit Value:
* AEL is DuPont's Accepta lower than the AEL are in a	effect, such limi	ts shall take pre	vernmentally imposed occupational exposure limits which are ecedence.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Color Odor pH Melting point/range Boiling point Vapour Pressure	<ul> <li>: liquid</li> <li>: colourless</li> <li>: slight, ether-like</li> <li>: neutral</li> <li>: ca84.0 ℃ (-119.2 ℉)</li> <li>: 55 ℃ (131 ℉)</li> <li>: 248 hPa at 20 ℃ (68 ℉)</li> <li>: 313 hPa at 25 ℃ (77 ℉)</li> </ul>
Density	: $854 \text{ hPa at } 50 \ ^{\circ}\text{C} (122 \ ^{\circ}\text{F})$
Density	: $1.60 \text{ g/cm3 at } 20 \ ^{\circ}\text{C} (68 \ ^{\circ}\text{F})$
Water solubility	: $1.58 \text{ g/cm3 at } 25 \ ^{\circ}\text{C} (77 \ ^{\circ}\text{F})$
Partition coefficient: n-	: ca. $0.10 - 0.14 \text{ g/l at } 20 \ ^{\circ}\text{C} (68 \ ^{\circ}\text{F})$
octanol/water	: POW: 2.7 at 20 \ ^{\circ}\text{C} (68 \ ^{\circ}\text{F})

<b>DuPont<sup>™</sup> VERTREL<sup>®</sup> XF sp</b> Version 4.1			
Revision Date 02/06/2014		Ref. 13000000559	
SECTION 10. STABILITY AND REACT			
Hazardous decomposition	<ul> <li>No decomposition if stored and applied as directed.</li> <li>Hazardous decomposition products formed under fire conditions.: Fluorinated hydrocarbons, Hydrogen fluoride, Carbon dioxide (CO2), Carbon monoxide</li> </ul>		
SECTION 11. TOXICOLOGICAL INFO DuPont <sup>™</sup> VERTREL <sup>®</sup> XF specialty Further information		Inhalation of vapours in high concentration may cause shortness of	
1,1,1,2,2,3,4,5,5,5-Decafluoropentane Dermal LD50	:	breath (lung oedema). > 5,000 mg/kg , rabbit	
Oral LD50	:	> 5,000 mg/kg , rat	
Inhalation 4 h LC50	:	114 mg/l , rat Central nervous system effects Convulsions	
Skin irritation	:	No skin irritation, rabbit	
Eye irritation	:	No eye irritation, rabbit	
Skin sensitization	:	Did not cause sensitisation on laboratory animals., guinea pig	
Repeated dose toxicity	:	Inhalation rat	
		No toxicologically significant effects were found.	
Aquatic Toxicity 1,1,1,2,2,3,4,5,5,5-Decafluoropentane 96 h LC50	<b>10ITA</b> :	N Oncorhynchus mykiss (rainbow trout) 13.9 mg/l	
		6/8	



## DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid Version 4.1 Revision Date 02/06/2014 Ref. 13000000559 96 h LC50 : Pimephales promelas (fathead minnow) 27.2 mg/l 96 h LC50 Danio rerio (zebra fish) 13 mg/l : 72 h EC50 Pseudokirchneriella subcapitata (green algae) > 120 mg/l 48 h LC50 Daphnia magna (Water flea) 11.7 mg/l : 21 d NOEC Daphnia magna (Water flea) 1.72 mg/l : **Environmental Fate** 1,1,1,2,2,3,4,5,5,5-Decafluoropentane Biodegradability : Not readily biodegradable. Bioaccumulation Bioaccumulation is unlikely. SECTION 13. DISPOSAL CONSIDERATIONS Waste Disposal : Can be used after re-conditioning. If recycling is not practicable, dispose of in compliance with local regulations. The product should not be allowed to enter drains, water courses or the soil. **Environmental Hazards** : If recycling is not practicable, dispose of in compliance with local regulations. SECTION 14. TRANSPORT INFORMATION Not classified as dangerous in the meaning of transport regulations. SECTION 15. REGULATORY INFORMATION TSCA : Listed 1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is 7/8

Material Safety Data Sheet



## DuPont<sup>™</sup> VERTREL<sup>®</sup> XF specialty fluid

Version 4.1

Revision Date 02/06/2014	Ref. 13000000559
	controlled by TSCA Section 5, Significant New Use Rule (SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal and film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.
SARA 313 Regulated Chemical(s)	SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

#### **SECTION 16. OTHER INFORMATION**

Vertrel<sup>®</sup> Before use read DuPont's safety information. For further information contact the local DuPont office or DuPont's nominated distributors. DuPont<sup>™</sup> Vertrel<sup>®</sup> are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

Contact person

: MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE 19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.